# trinamiX NIR Spectroscopy Solution **Model SYS-IR-R-P**



## **Spectroscopic specifications**

Spectral range	1450 – 2450 nm
Spectral resolution	1 % of wavelength, e.g. 15 nm at 1500 nm
Signal to Noise Ratio	>5.000 per spectral resolution element

## **Optical Components**

Detector	256 pixel PbS line array detector
Lamp Module	6 Tungsten halogen lamps
	Lifetime > 100.000 scans (typically)
	Replaceable by user
Sample interface	Scratch resistant sapphire window

## **Physical specifications**

Dimensions	152 mm x 84 mm x 42mm
Weight	570 g
IP class	IP65 dust- and waterproof (splash and jet water)

### **Environmental conditions**

Operating temperature	0°C – 40°C
	0 °C – 30°C for charging
Storage temperature	-20 °C – 60 °C
Air humidity (non-condensing)	20 % – 80 % (operation) / 20 % – 90 % (storage).
Height above sea level	≤2000 m
Type of use	Indoor and outdoor (operation), indoor (charging)

trinamiX GmbH Contact
Industriestr. 35 W www.trinamixsensing.com

67063 Ludwigshafen E info@trinamix.de

Germany

Release Date: 12th October 2021

# trinamiX NIR Spectroscopy Solution Model SYS-IR-R-P



# **Electrical specifications**

Power Input (for charging)	USB PD with 15 VDC, max. 2.75 A via USB type C connector
USB-Connection (for stationary use)	USB 2.0 communication via USB Type C connector
Wireless connection (for handheld use)	Wireless low energy via integrated antenna

### **Battery**

Туре	Rechargeable lithium-ion battery
Number of scans per battery charge	> 6.000
Nominal voltage	11.1 V
Nominal capacity	2600 mAh
Charging current	1300 mA
Transport classification	UN class: 9
	UN number: 3480, Lithium-Ion Battery
	Energy of battery: <100 Wh

### **Radio Frequency Module**

The device contains the following radio frequency (RF) module:

Туре	Würth Proteus-I AMB2621 / 2608011024000
Frequency range	2.44 GHz
Max. output power	Typ2 dBm, max. 0 dBm

Page 2/3 Internal





#### trinamiX GmbH

Industriestr. 35 67063 Ludwigshafen Germany This document, or any answers or information provided herein by trinamiX GmbH does not constitute a legally binding obligation of trinamiX GmbH. While the descriptions, designs, data and information contained herein are presented in good faith and believed to be accurate, it is provided for your guidance only. Because many factors may affect processing or application/use, we recommend that you make tests to determine the suitability of a product for your particular purpose prior to use. It does not relieve our customers from the obligation to perform a full inspection of the products upon delivery or any other obligation. No warranties of any kind, either express or implied, including warranties of merchantability or fitness for a particular purpose, are made regarding products described or designs, data or information set forth, or therefore the therefore the control of the products are used without infringing the intellectual property rights of others. In no case shall the descriptions, information, data or designs provided be considered a part of our terms and conditions of sale.